Use of this form serves as a Quality Assurance Agency Special Inspection Agreement between Building Official, Owner and Quality Assurance Agency for the purposes of special inspection per Section 22.02.515 of the Building Administrative Code of Clark County.



Development Services – Building Division

DISTRIBUTION:

1. JOB FILE

2. OWNER

3. CLARK COUNTY

4. QUALITY MANAGER

Form 811a

Eff. 03/29/10

Development Services Building Division

4701 W. Russell Rd • Las Vegas NV 89118 (702) 455-3000 • Fax (702) 221-0630 Ronald L. Lynn, Director/Building Official

| Report No. | |
|---------------|----|
| Page | of |
| Inspection | |
| Date | |
| Permit | |
| No. | |

POST-INSTALLED ADHESIVE ANCHORAGE CLEARANCE REPORT

| Duning Address. | I I I I I I I I I I I I I I I I I I I | ot. | Dlast | | |
|--|--|---------------------------------|-------------|-------------|--|
| Project Address: | I | Lot: | Block | <u>(; </u> | |
| Development Name: | | | | | |
| Quality Assurance Agency: | Owner/Ag | gent: | | ъ. | |
| Owner/Agent Signature: | | | | Date: | |
| CCBD Inspector Initials | | | | Date: | |
| 1 ST INSTALLATION INSPECTION SU | MMARV | | | | |
| INSPECTION ITEM RESULTS | INSPECTION | ITEM | RESU | LTS | |
| CCDDS-BD Plan Approval Date: | Quantity of Rod | | | | |
| CCDDS-BD Plan Sheet & Detail | Hole Depth & D | iameter: | | | |
| Adhesive Product Name: | Anchor Diamete | Anchor Diameter, Type & Length: | | | |
| Adhesive Expiration Date: | Anchor Embedn | | | | |
| Evaluation Report No. & Date: | Anchor Spacing | Anchor Spacing | | | |
| Concrete Type and Strength | Anchor Edge Di | stance | | | |
| Concrete Thickness & Temp (°F) | Time of Installat t cure,full (time | | | | |
| Hole Cleaning Procedure | | | | | |
| The special inspector must be present at the tir LOCATIONS OF ROD/BOLT & ADDI' | · | NFORMA' | TION | | |
| I hereby acknowledge that I have reviewed the a evaluation report, and manufacturers' installation the products and observed the product installation has been verified to be in accordance with the mainstructions, the above referenced evaluation repapproved plans. SPECIAL INSPECTOR (PRINTED) | on instructions. I inspected on. The anchor installation anufacturer's published | EN | IGINEER STA | MP HERE | |
| SPECIAL INSPECTOR (SIGNATURE) | DATE | | | | |
| Return completed certification to Clark County | Department of | | | | |

Use of this form serves as a Quality Assurance Agency Special Inspection Agreement between Building Official, Owner and Quality Assurance Agency for the purposes of special inspection per Section 22.02.515 of the Building Administrative Code of Clark County.



Development Services Building Division

4701 W. Russell Rd • Las Vegas (702) 455-3000 • Fax (702) 22

| NV 89118 | |
|----------|---|
| 21-0630 | |
| 21-0030 | Г |
| | |

| Report No. | |
|---------------|----|
| Page | of |
| Inspection | |
| Date | |
| Permit | |
| No. | |

| Ronald L. Lynn, | , Director/Building Official | L | No. | | |
|--|------------------------------|---------|---------|---------|-------|
| POST-INSTALLED ADHES | IVE ANCHORAGE | E CLEA | RANC | E REP | ORT |
| Project Address: | | Lot: | | Block: | |
| Development Name: | | | | | |
| Quality Assurance Agency: | Owner/A | Agent: | | | |
| Owner/Agent Signature: | <u>.</u> | | | | Date: |
| CCBD Inspector Initials | | | | | Date: |
| * | | | | | • |
| ND | | | | | |
| 2 ND INSTALLATION INSPECTION SUM | MARY | | | | |
| INSPECTION INFORMATION RESULTS | | | | | |
| Time of Torquing & t cure (time elapsed) | | | | | |
| Quantity Installed & Type: | | | | | |
| Quantity sustained to the state of the state | | | | | |
| Tightening Torque for Each Bolt | | | | | |
| | | | | | |
| Reference the 1 st Installation Inspection Summary Reports | | | | | |
| Inspection Summary Reports | | | | | |
| Serial Number of the Torque | | | | | |
| Wrench and Date of Calibration | | | | | |
| | | | | | |
| The special inspector must be present at the time | the bolt is torqued. | | | | |
| I OCATIONS OF DOD/DOLT & ADDITIONS | ONAL INCRECTION | INIEODM | ATION | | |
| LOCATIONS OF ROD/BOLT & ADDITIONS | UNAL INSPECTION | INFORM | ATION | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| I hereby acknowledge that I have reviewed the appr | | | | | |
| evaluation report, and manufacturers' installation i | - | | ENGINEE | R STAMP | HERE |
| the products and observed the product installation. has been verified to be in accordance with the manu | | | | | |
| instructions, the above referenced evaluation report | - | | | | |
| approved plans. | and the Clark County | | | | |
| | | | | | |
| | | | | | |
| SPECIAL INSPECTOR (PRINTED) | | | | | |
| | | | | | |
| SPECIAL INSPECTOR (SIGNATURE) | DATE | | | | |
| | | | | | |
| Return completed certification to Clark County D | epartment of | | | | |

Form 811b Eff. 03/29/10 **DISTRIBUTION:** 1. JOB FILE

Development Services – Building Division

2. OWNER

3. CLARK COUNTY

4. QUALITY MANAGER

POST-INSTALLED ADHESIVE ANCHOR CLEARANCE PROCEDURE

SPECIAL CASES: C-E

THIS FORM IS AVAILABLE AT THE CLARK COUNTY DEPARTMENT OF DEVELOPMENT SERVICES BUILDING DIVISION WEB SITE AND LISTED PRIME AGENCIES

- 1. The clearance report shall be used for post installed adhesive anchorage systems as identified in the approved plans and used as an alternate to the specified cast-in-place anchor.
- 2. The quality assurance agency special inspector shall complete the report for the work performed and leave a copy with the general contractor or permit holder. (At this point an engineer from the special inspection agency will not have sealed the report.)
- 3. The special inspector must be present at the time the bolt is torqued.
- 4. After the 1st and 2nd inspection has been completed, the report shall be given to the Clark County Department of Development Services Building Division (CCDDS-BD) Inspector as assurance that adhesive anchorage system installations have been inspected and accepted by the Quality Assurance Agency (QAA), prior to or at shear wall inspection.
- 5. The CCDDS-BD inspector shall initial the reports then place the reports into a designated basket in the inspections office. The designated basket will be located at the public counter.
- 6. A Building Permit Specialist shall enter the clearance requirement for adhesive anchorage into the required inspection screen for the permit listed on the form. The clearance shall be established at the hold point prior to a framing inspection.
- 7. The structural group will review and disposition the engineer sealed adhesive anchorage report. Both the field copies and the engineered sealed copies must be received by CCDDS-BD staff prior to the removal of the hold point.
- 8. The engineer sealed reports form shall be sent to CCDDS-BD records by the CCDDS-BD staff.

Adhesive Anchorage of Rods/Bolts Form - Web Address

http://dsnet.co.clark.nv.us/dsweb/bldg_pdfforms/qaa_rodsboltsreport.pdf

Form 811 DISTRIBUTION: 1. JOB FILE 2. OWNER 3. CLARK COUNTY 4. QUALITY MANAGER